

# RAZ- AT

Specification	Raz- AT
TILT FUNCTION	Gas spring assisted, up to 40° tilt range
RECLINE FUNCTION (Optional)	Gas spring assisted, up to 30°
SEAT WIDTH (Standard)	18"
SEAT DEPTH	16" or 19"
SEAT ADJUSTMENT	Up to 2" (fore/aft)
SEAT HEIGHT (Seat to floor height w/ molded seat)	21" - 25"
TOILET CLEARANCE HEIGHT Under pan brackets: Under frame:	16 ½" - 20 ½" 17 ½" - 21 ¾"
TOILET CLEARANCE WIDTH (Standard)	15 ¾"
BACK HEIGHTS Fixed Backs Adjusta-Backs	(From top of back support to top of molded seat) 17" (Z505) 20" (Z506T) 17" (Z510) 20" (Z515) 24" (Z520)
ARMREST HEIGHT (Armpad to top of molded seat)	8 ½" (Z505) 9 ½" (Z506T) 7" - 9 ½" (Z510) 8" - 10 ½" (Z515) 8" - 10 ½" (Z520)
WIDTH BETWEEN ARMPADS	18 ¾"
LATERAL SUPPORT (Adjustment range)	1 1/4" - 2 ½" offset (15 ½" - 13" trunk width) 2" vertical 1" fore/aft ± 5° pad angle
FOOTREST ADJUSTMENT (From seat to footplate)	16" - 20 ½" (Z705N) 18" - 22 ½" (Z705N w/ Z7FREXT)
CASTER TYPE AND SIZE	Dual-locking 5" casters ( X4)
OVERALL WIDTH	22 ½" (w/ std. armpad) 25 ½" (w/ Z715 armpad)
OVERALL LENGTH WHEN UPRIGHT Without footrests: With footrests:	33 ½" 43 ¼"
OVERALL LENGTH WHEN TILTED Without footrests: With footrests:	41 ½" 51 ¼"
WEIGHT CAPACITY	350 lbs.
PRODUCT WEIGHT	65 lbs.
FRAME AND HARDWARE MATERIAL	Stainless Steel

There is a two year limited warranty on the frame against manufacturing defects.  
The warranty is one year for all other components subject to normal wear and tear exclusions.

\*Prices, specifications, and options are subject to change without prior notice.