

Raz-AT600

| Specification | Raz-AT600 |
|--|--|
| TILT FUNCTION | Pressurized Locking Gas Spring with Weight Assist Spring System (WASS) up to 25° tilt range |
| WEIGHT ASSIST SPRING SYSTEM (User weight range) | 275 to 450 lbs. (125 to 205 kg) 400 to 600 lbs. (180 to 272 kg) |
| FRAME WIDTH (Seat and back frame) | Standard: 22" (56 cm) / Custom: Up to 30" (76 cm) |
| SEAT WIDTH (Commode seat) | Standard: 23" (58 cm) / Custom: 22" (56 cm) up to 32" (81 cm) |
| OVERALL WIDTH (With standard armpad) | = Frame width plus 2.75" (7 cm) |
| SEAT DEPTH (Front of back post to front of seat) | Standard: 18" (46 cm) / Custom: 16" (40 cm) up to 20" (51 cm) |
| SEAT ADJUSTMENT | Fore/Aft: Up to 2" (5 cm) / Lateral: up to 3/4" (2 cm) |
| BACK POSITION (C.O.G.) ADJUSTMENT | Fore/Aft: 2" (5 cm) |
| SEAT HEIGHT (With standard molded seat) | 22.5" - 23.5" (57 - 60 cm) |
| TOILET BOWL CLEARANCE HEIGHT Under frame: Under commode pan brackets: | 18.25" / 19.25" (46 / 49 cm) 18" / 19" (46 / 48 cm) |
| TOILET BOWL CLEARANCE WIDTH | Frame width less 5" (12.7 cm) |
| BACK HEIGHT | 21" (53 cm) |
| BACK ANGLE | Adjustable: 90° or 97° |
| ARMREST HEIGHT | Adjustable: 9" - 10" (23- 25 cm) |
| DISTANCE BETWEEN ARM PADS | Frame width plus 0.75" (2 cm) |
| LATERAL SUPPORT ADJUSTMENT RANGE | Offset: 0 - 2.25" (0 - 5.7 cm) Trunk Width: = Frame width less 0 to 4.5" (less 0 - 11.4 cm) Vertical: 2.5" (5 cm) Fore/Aft: 1" (2.5 cm) Pad Angle±: 5° |
| FOOTREST ADJUSTMENT (From seat to footplate) | Standard Z709: 16" - 20.5" (41 - 52 cm) Z709 with Z7FREXT: 18" - 22.5" (46 - 57 cm) |
| CASTER TYPE AND SIZE | Dual-locking 6" (15 cm) |
| OVERALL LENGTH WHEN UPRIGHT With Z709 footrests Without footrests | 42" - 43" (106 - 109 cm) 32.5" (82 cm) |
| OVERALL LENGTH WHEN TILTED With Z709 footrests* Without footrests* *Add 1.8" (4.5 cm) for 20"D Seat | 47" - 55" (119 - 140 cm) 35" - 43" (89 - 109 cm) |
| PRODUCT WEIGHT | 85 lbs. (39 kg) |
| FRAME AND HARDWARE MATERIAL | Stainless Steel (Lifetime warranty against corrosion) |

There is a two year limited warranty on the frame against manufacturing defects.
The warranty is one year for all other components subject to normal wear and tear exclusions.

*Prices, specifications, and options are subject to change without prior notice.